



TO:

DATE:

FROM:

PAGE: OF

CHANNEL SECECTION TABLE FOR SD-125

ADDITIONAL INFORMATION FOR SD125 WITH DB15 HIGH DENSITY CONNECTOR (NO MODEM)

| CHANNEL | 1 | 2 | 3 | 4 |
|--------------|--------|--------|--------|--------|
| 1 | HIGH | HIGH | HIGH | HIGH |
| 2 | HIGH | HIGH | HIGH | LOW |
| 3 | HIGH | HIGH | LOW | HIGH |
| 4 | HIGH | HIGH | LOW | LOW |
| 5 | HIGH | LOW | HIGH | HIGH |
| 6 | HIGH | LOW | HIGH | LOW |
| 7 | HIGH | LOW | LOW | HIGH |
| 8 | HIGH | LOW | LOW | LOW |
| 9 | LOW | HIGH | HIGH | HIGH |
| 10 | LOW | HIGH | HIGH | LOW |
| 11 | LOW | HIGH | LOW | HIGH |
| 12 | LOW | HIGH | LOW | LOW |
| 13 | LOW | LOW | HIGH | HIGH |
| 14 | LOW | LOW | HIGH | LOW |
| 15 | LOW | LOW | LOW | HIGH |
| 16 | LOW | LOW | LOW | LOW |
| DB15 PIN OUT | PIN 12 | PIN 13 | PIN 14 | PIN 15 |

NOTE: HIGH = LINK OPEN OR CHANNEL SELECTOR LINE NOT SHORT TO GROUND
 LOW = LINK CLOSED OR CHANNEL SELECTOR LINE SHORT TO GROUND

- THE NUMBERS 1, 2, 3, 4 IN THE TABLE ABOVE REFERS TO THE INTERNAL CHANNEL SELECTION DIPSWITCHES.
- TEST BOX IS AVAILBLE FROM MAXON ELECTRONICS, IF BENCH TESTING AND SERVICING OF THIS UNITS ARE TO BE PERFORMED.
- TO SOFTWARE PROGRAM THESE UNITS, A SPECIAL ADAPTOR (SD-010) IS REQUIRED, AND THIS ALSO CAN BE PURCHASED FROM MAXON ELECTRONICS.
- PLEASE NOTE THESE UNITS ARE DIFFERENT FROM THE SD-125 WITH INBUILT MODEMS, WHICH COME WITH DB15 HIGH DENSITY CONNECTORS AS WELL (THE ONLY WAY TO DIFFERENTIATE BETWEEN THESE RADIO AND THE ONES WITH MODEM, ARE THAT THE MODEM RADIOS HAVE AN EXPANDED COVER LID).

PLEASE CONTACT THE TECHNICAL DEPARTMENT AT MAXON ELECTRONICS AUSTRALIA PTY LTD FOR FURTHER INFORMATION ON +61 2 8707 3000.